

# GIUNTI ROTANTI

## IN LINEA

Per ugelli pesanti e bilanciati, guide di centraggio, idropistole.



Raccordo	1/4"	3/8"	1/2"	3/4"	1"	1" 1/4	1" 1/2
<b>Pressione Max (bar)</b>	400	400	300	300	300	250	200
<b>Giri/min</b>	6	6	6	6	6	6	6
<b>Dimensioni (mm)</b>	63 x 30 x 30	66 x 35 x 35	73 x 36 x 36	80 x 46 x 46	90 x 60 x 60	98 x 60 x 60	108 x 70 x 70
<b>Peso (gr)</b>	210	292	332	546	1008	1140	1680
<b>Codice</b>	<b>5030.06A</b>	<b>5030.10A</b>	<b>5030.15A</b>	<b>5030.20A</b>	<b>5030.25A</b>	<b>5030.32A</b>	<b>5030.38A</b>

## A 90°

Per rotazioni intermittenti o a media/bassa velocità.



Raccordo	3/8"	1/2"	3/4"	1"	1" 1/4
<b>Pressione Max (bar)</b>	210	210	210	210	180
<b>Dimensioni (mm)</b>	98 x 50 x 36	108 x 56 x 39	122 x 62 x 47	144 x 78 x 56	-
<b>Peso (gr)</b>	538	636	954	1694	1722
<b>Codice</b>	<b>5035.10A</b>	<b>5035.15A</b>	<b>5035.20A</b>	<b>5035.25A</b>	<b>5035.32A-1</b>