



Overview

Pvc hose reinforced with an anti-shock rigid Pvc spiral.

Characteristics

COLOUR:

light blue with an extruded red stripe.

TEMPERATURE RANGE:

- 25°C + 60°C

FEATURES:

Pvc hose reinforced with an anti-shock rigid Pvc spiral. Special formulation particularly suitable to be used at low temperatures. Inside surface smooth, light corrugation outside. Strong and flexible, resistant to crushing, abrasion, atmospheric agents and most chemicals.

APPLICATIONS:

excellent for suction in general, particularly suitable to be used on tank trucks thanks to its physical and mechanical features

Technical Specifications

DN (mm)	50	60	80	90	100
Thickness (mm)	4.3 - 4.9	4.5 - 5.2	6.0	6.3	7.3
Weight (g/m)	980	1230	1820	2120	2660
Bending radius (mm)	200	240	320	360	410
Working Pressure (bar)	4	4	3	3	3
Vacuum (m H2O)	10	9	9	9	9
Coil length (m)	50	50	50/30	50	50

Items

Part No.	Description
2031.50-50	APOLLO SE DN50 SUCTION HOSE, 50 MT COIL
2031.80-30	APOLLO SE DN80 SUCTION HOSE, 30 MT COIL
2031.90-30	APOLLO SE DN90 SUCTION HOSE, 30 MT COIL
2031.100-30	APOLLO SE SUCTION HOSE DN 100 30 M REEL