



## Overview

Used for industrial debris retrieval, for fixed or non-permanent installations.



## Characteristics

- Substrate: wear resistant NR, black smooth
- Reinforcement: threads of synthetic fabric with a steel spiral embedded in the wall
- Cover: weather resistant NR, black, grooved look
- Working Temp.: -30°C + 80°C

## APPLICATIONS

Pneumatic suction or delivery of abrasive powders or granular products.

# Technical Specifications

|                          |       |       |       |       |
|--------------------------|-------|-------|-------|-------|
| DN (mm)                  | 80    | 100   | 110   | 150   |
| Thickness (mm)           | 8,0   | 8,0   | 8,0   | 8,5   |
| Weight (g/m)             | 3160  | 3800  | 4150  | 6260  |
| Bending Radius (mm)      | 160   | 200   | 220   | 300   |
| Working Pressure (bar)   | 1,5   | 1,5   | 1,5   | 1,5   |
| Bursting Pressure (bar)  | 4,5   | 4,5   | 4,5   | 4,5   |
| Standard roll length (m) | 10/20 | 10/20 | 10/20 | 10/20 |

## Items

| Codice   | Descrizione                    |
|----------|--------------------------------|
| 2009.80  | Aspivrac-S Suction Hose DN 80  |
| 2009.100 | Aspivrac-S Suction Hose DN 100 |
| 2009.110 | Aspivrac-S Suction Hose DN 110 |
| 2009.150 | Aspivrac-S Suction Hose DN 150 |