



Overview



HP hoses for water specifically designed for sewer cleaning. The latest technologies have been applied in the production and the experience in the field result in high quality, reliability and capability of the products to satisfy the requirements of the sector. They are Made in Italy!

Characteristics

- Abrasion and wheather resistance synthetic rubber with single (1SC) or double (2SC) steel wire braids reinforcement.
- Temperature range from -30°C to +80°C
- Working/bursting pressure ratio 2,5:1
- Lowest friction coefficient in its class thanks to a new internal finishing, specifically designed for water application.
- The new formulated abrasion resistance smooth external cover exceeds 10 times the ISO 6945 standard
- Standard Lengths available upon request
- Several fittings options available upon request

Technical Specifications

DN	3/8"	1/2"	3/4"	1"
Steel Braid	Single (1SC)	Double (2SC)	Double (2SC)	Double (2SC)
I. D. (mm)	9,5	12,7	19	25,4
O. D. (mm)	15,7	20,4	27,6	35,8
W. P. (bar)	310	310	300	280
B. P. (bar)	1000	1240	960	840
Weight (kg/m)	0,248	0,521	0,764	1,171
B. R. (mm)	60	80	100	130

Items

3/8" hoses

Part No.	Description
T1.08.06-XXX	LONG LIFE HOSE 1SC 3/8' 310 BAR PER MT WITHOUT FITTINGS
T1.08.06-X20	LONG LIFE HOSE 1SC 3/8' 310 BAR 20 MT WITHOUT FITTINGS
T1.08.06-X30	LONG LIFE HOSE 1SC 3/8' 310 BAR 30 MT WITHOUT FITTINGS

1/2" hoses

Part No.	Description
T1.08.08-XXX	LONG LIFE HOSE 1SC 1/2' WITHOUT FITTINGS
5929.12-40R	ONGLIFE HP HOSE 1/2" 40MT CONN.M-F 1/2" - 280 BAR
5929.12-60R	ONGLIFE HP HOSE 1/2" 60MT CONN.M-F 1/2" - 280 BAR
5929.12-60RF	ONGLIFE HP HOSE 1/2" 60MT CONN.F-F 1/2" - 280 BAR
5929.12-60RM	
5929.12-80R	ONGLIFE HP HOSE 1/2" 80MT CONN.M-F 1/2" - 280 BAR
5929.12-80RF	ONGLIFE HP HOSE 1/2" 80MT CONN.F-F 1/2" - 280 BAR

3/4" hoses

Part No.	Description
5929.34-80R	LOGLIFE HP HOSE 3/4" 80MT CONN.M-F 3/4" - 280 BAR
5929.34-80RF	LOGLIFE HP HOSE 3/4" 80MT CONN.F-F 3/4" - 280 BAR
5929.34-100RM	

1" hoses

Part No.	Description
5929.1-100R	LOGLIFE HP HOSE 1" 100MT CONN.M-F 1" - 280 BAR
5929.1-120R	LOGLIFE HP HOSE 1" 120MT CONN.M-F 1" - 280 BAR

GALLERY IMAGES

