



Overview

High efficiency cleaning nozzles with double jet type and angle:

- 45° fan jets ensure an all around cleaning action, covering the entire pipe section;
- 15° rear jets (w/ceramic inserts), to enable the nozzle to a proper traction.

Characteristics

Compatible with domestic drains, condo vertical pipes and municipal sewer cleaning, these nozzles can also be used before root cutter jobs or CCTV inspection. Using these nozzles with pipe centralizer you obtain a better cleaning action all around the pipe. RONDÒ

Technical Specifications

Inlet	1/2" F	3/4" F	1" F	1" F	1" 1/4 F
Ø x L (mm)	39 x 68	53 x 78	59 x 90	89 x 125	89 x 125
Weight (kg)	0,47	0.86	1.4	4.3	4.3
Fan Jets	6×45°	8×45°	9×45°	12×45°	12×45°
Rear Jets	3×20°	3×20°	3×20°	3×20°	3×20°
Inserts	M6x8 C	M6x8 C	M8	M12	M12
Maximum Pressure (bar)	300	300	300	300	300
Flow (lt/min)	95-150	115-190	170-265	230-340	230-340
Working DN (mm)	60-150	70-350	200-400	300-800	300-800

Items

Part Number	Description
3580.01	1/2" F RONDO' NOZZLE, DN40
3580.05	3/4" F RONDO' NOZZLE, DN50
3580.10	1" F RONDO' NOZZLE, DN60
3580.20	1" 1/4 F RONDO' NOZZLE, DN90

GALLERY IMAGES

