



Overview

Small nozzles with conical or round head and with or without front jet.



Characteristics

These nozzles are to be used with portable, trailer or skid mounted jetters, sewer cleaning vehicles for domestic drain and pipe cleaning.

Configurations with multiple front jets are available to increase the unblocking capacity.

In case even smaller nozzles are required for an easier headway in bent pipes, nozzles with hose fitting for direct crimping to the hose are available.

Technical Specifications

Inlet	1/8" F	1/8" F	1/8" F	1/8" F	1/4" F	3/8" F	3/8" M
Ø x L (mm)	15 x 15	15 x 15	15 x 15	15 x 15	18 x 29	23 x 31	21 x 37
Weight (gr)	8	8	8	8	25	40	50
Rear Jets	35°	35°	25°	25°	35°	35°	35°
Front Jets	-	1×0°	1×0° + 1×30°	1×0° + 3×30°	M4x5	M4x5	M4x5
Maximum Pressure (bar)	250	250	250	250	250	250	250
Flow (lt/min)	20-60	20-60	20-60	20-60	25-80	30-90	30-90
Working DN (mm)	20-60	20-60	20-60	20-60	25-125	35-150	35-150
Part Number	5500.07	5500.07A	5500.07F2	5500.07TR	3518.00	3519.00	3519.00M

Items

1/8" Nozzles

	Part No.	Description
	5500.07A	1/8" F SILE NOZZLE, conical head and front jet
	5500.07TR	1/8" F SILE NOZZLE, conical head and 4 front jets

1/4" Nozzles

	Part No.	Description
	3518.00TR	1/4" F SILE NOZZLE, with multiple front jets



3519.00

3/8" F SILE NOZZLE (delivered with M4 plug and additional insert for front jet)



3519.00A

3/8" F NOZZLE, only front jets



3519.00MTR

3/8" M SILE NOZZLE, multiple front jets

Nozzles with hose fitting

Part No.

Description



5500.01A

NOZZLE WITH FRONT JET AND FITTING FOR 3/16" HOSE



5500.012A

NOZZLE WITH FRONT JET AND FITTING FOR 1/4" HOSE

GALLERY IMAGES

