



Overview

Warthog nozzle, 1" F inlet, with controlled rotation and power of its jets



Characteristics

All the water is sprayed out from the rough few, but high quality inserts with flow straightener. The combination of these features makes these nozzles unique and indispensable for the toughest high pressure jobs. DS WARTHOG is 2 nozzles in 1: with standard configuration it can be used for unblocking application (grease, soap, limestone...); with DS configuration (2 x 85° jets) the nozzle is very aggressive for cleaning and descaling applications. These nozzles are offered as package in plastic case with double set of inserts and tools to change the configuration quickly. With special service and overhaul kits, these nozzles can be regularly serviced for long durability.

Technical Specifications

Inlet	1" F
Ø x L (mm)	106 x 230
Weight (kg)	4.9
Front Jet	1 x 15 °
Rear Jets	4 x 38°
Radial Jets (only DS head)	2 x 85°
Flow (lt/min)	190-300
Maximum Pressure (bar)	350
Working DN (mm)	200-900

Items

Nozzles

	Part No.	Description
	75000.60	1" WG WARTHOG NOZZLE
	75000.60D	1" WG WARTHOG NOZZLE, WITH DS HEAD (RADIAL JETS)

Maintenance Kit

	Part No.	Description
	ST.WG600V	SERVICE KIT FOR WARTHOG 1"
	ST.WG610V	OVERHAUL KIT (WG)
	ST.WG612	TOOL KIT (WG)

GALLERY IMAGES

