



Overview

Strengths of Warthog nozzles are controlled rotation and power of its jets



Characteristics

All the water is sprayed out from the rough few, but high quality inserts with flow straightener. The combination of these features makes these nozzles unique and indispensable for the toughest high pressure jobs.

These nozzles are offered as package in plastic case with double set of inserts and tools to change the configuration quickly.

With special service and overhaul kits, these nozzles can be regularly serviced for long durability.

- Only available in preconfigured options for the most common flows and pressures
- Field repairable
- Spare parts and components always available that make the nozzle fully rebuildable
- Newly designed centralizer, more resistance and with increased durability

UNIVERSAL

Jetted for an equal balance of pulling/flushing & cleaning/cutting action.

Technical Specifications

Inlet	3/4" F BSPP
Ø x L (mm)	130 x 230
Weight (kg)	2
Front Jet	1 x 15 °
Rear Jets	2 x 30°
Radial Jets (only Descaler Head)	2 x 85°
Flow (lt/min)	40-190
Working Pressure (bar)	350-550
Working DN (mm)	150-450
Recycling	No
Maintenance Interval	50-60 hr

Items

Nozzles

	Part No.	Description
	75000.55C	WARTHOG WH 3/4" F CLASSIC
	75000.55CD	WARTHOG WH 3/4" F PRO DESCALING 1@PLUG 2@105° 2@150°

Maintenance Kit

	Part No.	Description
	ST.WH600V	SERVICE KIT (WH)
	ST.WH610V	OVERHAUL KIT (WH)
	ST.WH612	TOOL KIT (WH)

GALLERY IMAGES

