



Overview

Strengths of Warthog nozzles are controlled rotation and power of its jets



Characteristics

All the water is sprayed out from the rough few, but high quality inserts with flow straightener. The combination of these features makes these nozzles unique and indispensable for the toughest high pressure jobs.

These nozzles are offered as package in plastic case with double set of inserts and tools to change the configuration quickly.

With special service and overhaul kits, these nozzles can be regularly serviced for long durability.

Technical Specifications

Inlet	1/2" F
Ø x L (mm)	48 x 76
Weight (kg)	1.33
Front Jet (nr. x angle)	1 x 15°
Radial Jets (nr. x angle)	2 x 85°
Rear Jets (nr. x angle)	2 x 30°
Flow (lt/min)	27-75
Maximum Pressure (bar)	350
Working Pressure (bar)	100-350
Rotation (rpm)	200-500
Pull (N)	40-120
Working DN (mm)	100-200

Items

Nozzles

Part No.	Description
75000.50C	WARTHOG WS 1/2" F BSPP CLASSIC
75000.50B	WARTHOG WS 1/2" F PRO, WITH WHIP HOSE WHIP HOSE
75000.50TC	WARTHOG WS 1/2" F CLASSIC, WHIT WHIP HOSE

Service Kit

Part No.	Description
ST.WS600	SERVICE KIT (WS)
ST.WS610	OVERHAUL KIT (WS)
ST.WS612	TOOL KIT (WS)

Centralizers

Part No.	Description
ST.WS085	WS CENTRALIZER CAGE(ALONE)

GALLERY IMAGES

