



Overview



The WT Classic is built to navigate elbows and bends in 3-6" pipes with roots, ice, and other blockages. With carbide wear buttons that extend nozzle life, the WT will boost your cleaning abilities through laterals at homes, buildings, restaurants, and other commercial facilities. This tool is most commonly used on small capacity pumps and cart jetters.

Characteristics

Features

- Ball design reduces hang-ups
- Maneuverable in multiple elbows
- Repairable and rebuildable, field serviceable
- Durability extended by specially designed carbide buttons

Technical Specifications

Inlet	3/8" F	1/2" F
Ø x L (mm)	48 x 76	48 x 86
Weight (kg)	0.54	0,54
Tipo inserti	AP2	AP2
Front Jet	1 x 15 °	1 x 15 °
Rear Jets	2 x 30°	2 x 30°
Radial Jets (only with DS head)	-	-
Flow (lt/min)	20-45	35-80
Maximum Pressure (bar)	350	350
Working DN (mm)	75-150	75-150

Items

Nozzles

Part No.	Description
75000.53C	WARTHOG WT CLASSIC 3/8" F
75000.54C	WARTHOG WT CLASSIC 1/2" F

Maintenance Kit

Part No.	Description
ST.WT610VS	WT OVERHAUL KIT WITH VISC AND SYRINGE
ST.WT600	SERVICE KIT (WT)
ST.WT602	SEAL KIT (WT)
ST.WT612	TOOLS KIT (WT)

GALLERY IMAGES

